

# WSG

## Weatherproof housing for blowdown units

The weatherproof housing is used for outdoor assembly of temperature and weather-sensitive units such as the blowdown unit Cooltrol data.

### BENEFITS

- Wide temperature application range for use in winter as well as in summer
- Incl. heater, fan and thermostat
- Simple assembly and commissioning

### APPLICATIONS

- Protection of the blowdown unit against weather, solar radiation and frost when installed outdoors



Blowdown unit in weatherproof housing WSG

# WSG

## Weatherproof housing for blowdown units

### DESCRIPTION

#### Scope of supply

- Plastic housing with viewing window
- Control cabinet heating (heat output 50 W,  $T_u = 10^{\circ}\text{C}$ )
- Control cabinet frost monitor ( $-20^{\circ}$  to  $+30^{\circ}\text{C}$ ) complete incl. mounting plate and wall mounting bracket
- Suitable for blowdown units Cooltrol data (MKB 15, MKB 20 und BP)

### CONDITIONS OF USE

The minimum distance between the heater and other components must be 50 mm. Option suitable exclusively for the desalination plants of the series Cooltrol data MKB 15. WSG for Cooltrol data MKB 25 available on request!

### TECHNICAL DATA OF SERIES

| Product name            | Mains connection | Dimensions in mm | Weight empty approx. | Item number |
|-------------------------|------------------|------------------|----------------------|-------------|
|                         | V / Hz           | W x D x H        | kg                   |             |
| <b>WSG with heating</b> | 230 / 50         | 600 x 300 x 850  | 25.0                 | 175 041     |