DESTILLO D 2 Mixed-bed water demin cartridges

Mixed-bed water demin cartridge filled with single-use resin in plastic design for pressureless operation (free pure water outlet).

BENEFITS

- No wastewater discharge
- Easy installation and fast cartridge replacement
- Delivery of complete units (cpl) incl. resin, conductivity meter, connection hoses, wall bracket and accessories
- Delivery of replacement cartridges (EP) incl. resin

APPLICATIONS

- Production of small pure water quantities for laboratories, doctors' surgeries and clinics
- Equally suitable for battery, heating or cooling systems



DESTILLO D 2 replacement cartridge and D 2 complete

DESTILLO D 2 Mixed-bed water demin cartridges

DESCRIPTION

DESTILLO D 2 cpl

Plastic cartridge with single-use resin filling. Conductivity meter LWM S D2 with connection cable, raw and pure water hose, screw connections 3/4", wall bracket, fixing material and packaging included.

DESTILLO D 2 EP

Plastic cartridge with single-use resin filling as replacement cartridge. Packaging included.

CONDITIONS OF USE

The device is designed for pressureless operation with city water and free pure water outlet.

TECHNICAL DATA OF SERIES

Operating pressure	_
Operating temperature	5 – 30 °C
Connection	R 3⁄4
Ambient temperature	0 - 40 °C

Product name	Hydr. output	Capacity at 300 μ S/cm	Dimensions in mm	Item number
Resin volume (I)	l/h	I.	D x H	
DESTILLO D 2 cpl	50	320	115 x 515	010 001
DESTILLO D 2 EP	50	320	90 × 390	010 002