

# UO 120 - 500

## Reverse osmosis units

The reverse osmosis stand-alone unit (wall mounting also possible) is used for the desalination of softened water with a salinity of up to 1,000 mg/l. It is equipped with a compact rotary vane pump. The RO 524 controller allows fully automatic operation without logging of operation data and with fixed, factory-set limit values.

### BENEFITS

- Available from stock
- Cost-effective, factory-preset RO 524 controller

### APPLICATIONS

- Desalination of softened water
- Suitable for commercial and industrial applications that do not require operation data logging and parametrisation



UO 500

# UO 120 - 500

## Reverse osmosis units

### DESCRIPTION

#### Reverse osmosis

- Base frame made of powder-coated sheet steel
- Pre-filter RO (5 µm) with two glycerine-filled pressure gauges
- High-pressure pump as rotary vane pump
- Low-pressure element(s) with PA/PS composite membranes in stainless steel pressure vessel(s)
- Connection cable (3 m) with 16 A - 6 h CEE plug, 3-pin
- Unit incl. piping and wiring, electrical construction acc. to VDE 0100 Part 600, VDE 0113 Part 1
- Unit tested, parameterised and conserved in own test field

#### Fittings and instrumentation

- Inlet solenoid valve and sampling valves for feed water and permeate
- Valves for adjusting the flow rates of permeate and concentrate
- Pressure switch for monitoring the feed water pressure and manometer for operating pressure
- Flow meter (rotameter) for permeate and concentrate
- Permeate conductivity measurement without temperature compensation
- Connection fittings for a manual cleaning system

#### RO 524 microprocessor controller

- Fully automatic monitoring and control of the unit, operation of the controller with switch
- Two-digit, alphanumeric display and two LEDs as local indication for operation and disinfection
- Integrated functions: external stop, tank full, error message due to lack of pressure and hard water, automatic restart with progressive restart times
- Automatic concentrate displacement after each operating phase, forced displacement after 24 h standstill

#### Available inputs (low voltage)

- Level permeate tank (1 or 2 float switches), hard water, external stop (e.g. if feed water supply interrupted)

#### Available outputs

- Connection softening unit (230 V/50 Hz), collective fault signal (floating changeover contact)

#### Programming options (only factory-preset by manufacturer)

- Conductivity limit value 50 µS/cm (range 1 -99 µS/cm)
- Conductivity advance warning 40 µS/cm (range 1 - 99 µS/cm)
- Conductivity limit value delay 5 min (range 1 - 250 min)
- Flushing interval / time when tank is full 24 h (range 1 - 250 h) / 15 min (range 1 - 99 min)
- Concentrate displacement time 60 sec (range 1 - 250 sec)

#### Optionally available

- Hardness control unit limitron to protect the membranes from hard water
- HR modules, PR permeate recirculation and VSE blending device

# UO 120 - 500

## Reverse osmosis units

### CONDITIONS OF USE

The unit may only be used for the desalination of softened feed water with drinking water quality or appropriately pre-treated well or surface water. The unit is designed for a salinity (TDS) of 1,000 mg/l and a temperature of 15 °C. Under these conditions, the projected permeate output is achieved even after three years of operation. The permeate yield depends on the raw water quality and the pre-treatment. The following parameters must be maintained in the feed water:

Free chlorine	not detectable
Iron (Fe)	< 0.2 mg/l
Manganese (Mn)	< 0.05 mg/l
Silica (SiO <sub>2</sub> )	< 25 mg/l
Silt density index (SDI)	< 3
Feed water temperature	5 – 35 °C
Feed water pressure	3 – 6 bar
Pressure fluctuation	± 0.5 bar

### TECHNICAL DATA OF SERIES

Controller	RO 524
Desalination rate min.	97 %
Permeate recovery	75 – 80 %
Permeate back pressure max.	0.3 bar
pH value operation	6.5 – 9.5
pH value cleaning	2 – 12
Ambient temperature	5 – 40 °C

Product name	Mains connection	Hydraulic connection	Dimensions in mm	Item number
Permeate l/h	kW / V / Hz	feed/permeate/conc.	W x D x H	
UO 120	0.55 / 230 / 50	DN 20 / DN 10 / DN 10	410 x 380 x 1,160	381 921
UO 300	0.55 / 230 / 50	DN 20 / DN 10 / DN 10	410 x 380 x 1,250	381 922
UO 500	0.55 / 230 / 50	DN 20 / DN 10 / DN 10	410 x 380 x 1,250	381 923